

## BACnet PTEC VAV with Series Fan and 3-Stage Electric Heat Controller



The BACnet PTEC VAV with Series Fan and 3-Stage Electric Heat provides high performance Direct Digital Control (DDC) of pressure-independent, variable-air-volume zone-level routines.

The BACnet PTEC VAV with Series Fan and 3-Stage Electric Heat can operate stand-alone or can be networked to perform complex HVAC control, monitoring and energy management functions and is designed to reside on any BACnet control system.

### Features

- Communicates using BACnet MS/TP protocol for open communications on BACnet MS/TP networks.
- BTL listed as a B-ASC device.
- Auto-discovery and Auto-addressing over entire MS/TP network.
- Programmable using PPCL.
- Setpoints and control parameters assigned and changed locally or remotely.
- Setpoints and control parameters stored in Electrically Erasable Programmable Read Only Memory (EEPROM)—no battery backup required.

- Returns from power failure without operator intervention.
- No calibration required, thereby reducing maintenance costs.
- Advanced digital room unit for temperature, CO<sub>2</sub>, and relative humidity.
- Supports analog or digital room unit with relative setpoint adjustment and either absolute or warmer-cooler setpoint adjustments.
- Applications in 550-492PA include a user-adjustable temperature offset for the room temperature reading when required for validation purposes.
- PID control of HVAC systems to minimize offset and maintain tighter setpoint control.
- Unique control algorithms for specific applications.
- Plenum rated controller.
- Reports airflow in cfm (lps).
- Meets low duct static pressure requirements.
- Separate minimum and maximum air volume setting for heating and cooling modes.
- Demand Control Ventilation minimum setpoint (controllable by PPCL).
- Separate minimum night flow setpoint to reduce energy.

### Applications

- Slave Mode (Application 6699)
- VAV with Series Fan and 3-Stage Electric Heat (Application 6657)

Control algorithms are pre-programmed. The controller is ready to operate after selecting the application. If desired, the operator may adjust the air volume setpoints in cfm (lps), room temperature setpoints and other parameters. The controller is

designed for operation and modification without vendor assistance.

If required, new custom code using PPCL programming language can be added to replace or supplement the standard application residing in the controller. This provides the flexibility to meet many job specifications with the assurance of having a proven and tested standard application to rely upon.

## Hardware

### Controller Board

The BACnet PTEC VAV with Series Fan and 3-Stage Electric Heat consists of an electronic controller assembly and on-board differential pressure sensor.

This controller provides all wiring terminations for system and local communication and power. The cable from the room sensor (purchased separately) connects to an RJ-11 jack on the controller. All other connections are removable terminal blocks. The controller assembly is mounted on a plastic track that mounts directly on the terminal box.

An optional enclosure (P/N 550-002) protects the controller assembly.

The controller interfaces with the following external devices:

- Floating or analog (0-10 Vdc) control valve and damper actuators
- Series Fan control with Intelligent Motor Controller that is provided by others
- Digital output devices (stages of heat, baseboard radiation)
- Temperature sensors (room and optional auxiliary temperature)
- Service and commissioning tools
- BACnet Building Automation System using network communications trunk
- Digital input devices (dry contacts from motion sensors, alarm contacts, switches)

### Combination Temperature, Carbon Dioxide, and Relative Humidity Models

The Series 2200/2300 range of BACnet Programmable TEC (PTEC) room units includes temperature only or combination temperature/humidity, temperature/CO<sub>2</sub>, or temperature/CO<sub>2</sub>/humidity models. For these models, all measurement variables—CO<sub>2</sub>, temperature and relative humidity values—are passed digitally to the PTEC. This information is passed from the room unit through the RJ-11 cable to the RTS port on the PTEC.



#### NOTE:

A CO<sub>2</sub> power module (product number AQM2200) is also needed for the CO<sub>2</sub> sensor option to function.

## VAV with Series Fan and 3-Stage Electric Heat Controller Specifications

Dimensions	4-1/8" W × 11-1/4" L × 1-1/2" H
Weight	approx. 3 lbs (1.35 kg)
Controlled Temperature Accuracy	±1.5°F (0.9°C)

Power Requirements	
Operating Range	24 Vac +/-20%, 50 or 60 Hz
Power Consumption	7 VA (plus 12 VA per DO)

Inputs	
Analog	1 room temperature sensor 1 velocity sensor <i>(Optional at RTS)</i> 1 setpoint 2 auxiliary temperature sensors (10K Ω thermistor) 1 selectable 0-10 Vdc/4-20 mA
Digital	2 dry contacts

Outputs	
Analog	3 0-10 Vdc, 5 mA maximum
Digital	8 DO 24 Vac optically isolated solid state switches @ 0.5 amp

Communications	
Remote	BACnet MS/TP (EIA 485), 9600 bps to 76800 bps FLN Trunk
Local	WCIS and PTEC Tool

Ambient Conditions	
Shipping & Storage Temperature	-13°F to 158°F (-25°C to 70°C)
Operating Temperature	32°F to 122°F (0°C to 50°C)
Humidity Range	5% to 95% rh (non-condensing)

Agency Listings	
UL Listing	UL 916, PAZX
cUL Listed	Canadian Standards C22.2 No. 205-M1983, PAZX7
FCC Compliance	47 CFR Part 15
BTL Listed	as a B-ASC device

## Optional Accessories

### Autozero Module

The optional Autozero Module (product number 540-380) should be used when continuous operation at occupied flow is required for an area. The Autozero Module is connected to the air velocity inlet ports of the controller and provides periodic recalibration of the air velocity transducer without changing air volume being delivered to a room. This recalibration ensures long-term precise airflow delivery.

### Autozero Module Specifications

Power Consumption	.75 VA @ 24 Vac max.
Dimensions	2" W x 1.51" H x 1.89" D (58 mm x 78 mm x 29 mm)
Weight	1.3 oz. (36.9 g)



*Autozero Module.*

## Differential Pressure Sensor

The differential pressure sensor is easily connected to the box's air-velocity sensing elements to provide measurement of the differential pressure. The measured value is converted to actual airflow in cfm (lps) by the controller.

### Differential Pressure Sensor Specifications

Temperature Range	32°F to 122°F (0°C to 50°C)
Measurement Range	0 to 5200 fpm (0 to 26 m/s)

## Pneumatic Transducer

An optional PTS Pneumatic Transducer provides the signal conversion from electronic to pneumatic. The module is piped to the pneumatic actuator and wired to the controller. This transducer provides for accurate control of pneumatic actuators for precise temperature and air volume control.

### Pneumatic Transducer Specifications

Maximum Input Pressure	30 psi (207 kPa)
Air Consumption	0 SCIM
Power Consumption	4 VA @ 24 Vac max.
Dimensions	3-1/2" L x 2-1/4" W x 1-1/2" H (87 mm x 57 mm x 38 mm)
Weight	9 oz (0.3 kg)

## Product Ordering Information

Description	Product Part Number
BACnet PTEC VAV with Series Fan and 3-Stage Electric Heat	550-492PA
Large enclosure for electronic controller without damper actuator (long board).	550-002

# Document Information

Technical Specification Sheets/Technical Instructions	Document Part Number
BACnet Protocol Implementation Conformance (PIC) Statement	149-1033
Room Temperature Sensors – Series 2200	149-601/149-820
Room Temperature Sensors – Series 2300	149-600/149-321
AQM2200 Power Module	129-111
Series 2200 Carbon Dioxide Room Units	129-609
Series 2300 Carbon Dioxide Room Units	129-608
Duct Temperature Sensor	149-134P25
Low Limit Detection Thermostat	155-016P25
Analog Sensors – 10K/100K Ohm Thermistor	149-262/149-982
QXA2601 Condensation Sensor	149-931
<b>Siemens Valves</b>	<b>Document Part Number</b>
599 Series Zone Valves 2-Way, 3-Way Zone Valve Electric	154-034
599 Series Zone Valves and Actuators – Modulating, On/Off Spring Return, 2-Position Control	154-063
<b>Siemens Electronic Actuators</b>	<b>Document Part Number</b>
OpenAir Electronic Damper Actuators, GDE/GLB Series Non-spring Return Rotary 24 Vac – Modulating Control 0 to 10 Vdc	155-187P25
OpenAir Electronic Damper Actuators, GDE/GLB Series Non-spring Return, 24 Vac Floating Control, Rotary	155-188P25
OpenAir GEB Series Non-spring Return, 24 Vac, 132 lb-in Rotary Electronic Damper Actuators	155-318P25

Information in this document is based on specifications believed correct at the time of publication. The right is reserved to make changes as design improvements are introduced. Product or company names mentioned herein may be the trademarks of their respective owners.  
 © 2015 Siemens Industry, Inc.

**Siemens Industry, Inc.**  
 Building Technologies Division  
 1000 Deerfield Parkway  
 Buffalo Grove, IL 60089-4513  
 USA  
 Tel. 1 + 847-215-1000

Your feedback is important to us. If you have comments about this document, please send them to [SBT\\_technical.editor.us.sbt@siemens.com](mailto:SBT_technical.editor.us.sbt@siemens.com).

Document No. 149-864  
 Printed in the USA  
**Page 4 of 4**