



PDU30MVT32F Metered PDU

Engineered to distribute UPS, generator or utility AC power to multiple devices, servers and network/telecom equipment.

The CyberPower 32-outlet (32 Front) 0U vertical rack mount metered power distribution unit (PDU30MVT32F) provides 120V 30A output. It distributes power to 32 NEMA 5-20R receptacles from a single NEMA L5-30P twist lock plug, with unfiltered electrical pass-through. The current draw for connected equipment is displayed in amps on the front of two LCDs for real-time load monitoring.

Designed for datacenters and other electrically demanding applications, this unit has a rugged, industrial-grade metal housing and a 10-foot AC power cord. It supports vertical, horizontal and wall mount installation, includes a cord retention tray and is ETL/RoHS certified.

A Lifetime Warranty ensures that this PDU is free of defects in design, assembly, material and workmanship.

Typical Applications

- Servers
- Network Devices
- Telecom Equipment

Features

- Metered PDU
- Real-Time Load Monitoring
- Industrial-Grade Metal Housing
- Lifetime Warranty

PDU30MVT32F Metered PDU

Engineered to distribute UPS, generator or utility AC power to multiple devices, servers and network/telecom equipment.

GENERAL	
Type	Metered PDU
Phase	Single Phase
INPUT	
Voltage	120V
Frequency	50Hz/60Hz
Maximum Input Current	30A (Derated to 24A)
Plug Type	NEMA L5-30P
Plug Style	Straight, Twist Lock
Cord Length	10'
OUTPUT	
Nominal Output Voltage	120V
Outlets - Total	32
Outlet Type	NEMA 5-20R
Outlets - Front	32
Outlets - Rear	0
Meter Readout	(2) Amperage
Overload Protection	20A x 2
PHYSICAL	
Rack Size	OU
Form Factors Supported	Vertical Rackmount, Wallmount
Cord Retention Organizers	Yes
External Site Ground Pin	Yes
Adjustable Mounting Brackets	3 sets (L-short, L-long, Flat)
Dimensions (WxHxD) (in.)	70 x 1.75 x 2.25
Weight (lbs.)	12.80
ENVIRONMENTAL	
Operating Temperature	32°F to 95°F / 0°C to 35°C
Operating Relative Humidity	0% - 95% non-condensing
Storage Temperature	5°F to 113°F / -15°C to 45°C
Maximum Operating Elevation	10,000 ft / 3,000 m
Maximum Storage Elevation	50,000 ft / 15,000 m
CERTIFICATIONS	
Safety	UL60950_1 certified by ETL (USA), CSA C22.2 (Canada)
Environmental	RoHS Compliant
WARRANTY	
Product Warranty	Lifetime