

cnReach™ N500 450 MHz Radio

For outdoor critical infrastructure operations, cnReach transports process monitoring and control data from the remote sensor back to the operations center supporting real-time automated decision making and on-going analytics. Covering large geographic areas, hard to reach terrain and challenging spectrum environments, cnReach delivers reliable, secure connectivity to the petrochemical, electric utility, water/wastewater/stormwater and transportation industries. cnReach eases the migration to modern networks by combining legacy serial and analog/digital I/O with TCP/IP and Ethernet connectivity.



cnReach N500 450 MHz Radio

Fully integrated into a ‘single pane-of-glass’ management platform (cnMaestro™) cnReach helps bridge the IT/OT sides of complex organizations. Combining cnReach’s licensed and unlicensed narrow-band radios with Cambium Networks’ broadband technologies, industrial organizations are delivering end-to-end Industrial Internet of Things solutions today.

- Licensed 450 MHz (406-430 and 450-470 MHz) (cnReach is also available in 900 MHz and 700 MHz)
- Up to 8W transmit (39 dBm) in FCC and Up to 2W transmit (33 dBm) in ETSI
- Point-to-point, Point-to-multipoint and Relay configurations in same hardware
- Secure communications with AES 128/256-bit encryption and password authentication
- Highly reliable communications with access point synchronization and adaptive modulation
- Single and dual radio configurations for advanced back-to-back relay topologies.
- Extensive I/O capabilities easing the transition from serial to all-IP networks with multiple serial ports, Ethernet ports and analog/digital I/O built-in.
- Sophisticated network planning with LINKPlanner, a no-charge planning tool enabling network designers to predict both capacity and availability of networks crossing all of Cambium’s technologies.
- Supported by cnMaestro software for monitoring the status of entire networks carrying traffic across sensors

PRODUCT	PRODUCT DESCRIPTION	FCC MODEL NUMBERS	ETSI MODEL NUMBERS
	N500 450 MHz Single	NB-N500410A-US	NB-N500410A-EU
	N500 450 MHz Single with IO	NB-N500411A-US	NB-N500411A-EU
	N500 450 MHz Dual	NB-N500420A-US	NB-N500420A-EU
	N500 450 MHz Dual with IO	NB-N500421A-US	NB-N500421A-EU
	N500 IO Expander	NB-N500001A-US	NB-N500001A-EU

DEPLOYMENT TOPOLOGIES

	Point to Point (PTP)
	Point to Multipoint (PMP)
	Repeater (REP) - Single or Dual Radio
the-air signalling rate.	Stand-alone IO Expander

** At 8W output transmit duty cycles are reduced depending on operating conditions.

RADIO PERFORMANCE

Frequency Range	406-430 MHz and 450-470 MHz
Output Power	50 mW to 8W (10 dBm to 39 dBm) for FCC; 50 mW to 2W (33 dBm) for ETSI
Step Size	10 mW
Modulations	MSK / QPSK / 8PSK / 16QAM / 32QAM
Capacity*	9.6 kbps to 56.7 kbps RF data rate; up to 30 kbps UDP throughput in 12.5 kHz channels
Channel Bandwidths	12.5 kHz (25 / 50 / 100 kHz available regulations permitting)
Range	Up to 70 miles

RECEIVE SENSITIVITY

12.5 KHZ CHANNEL - FCC

12.5 KHZ CHANNEL - ETSI

	Rx Sensitivity (dBm)	Capacity* (kbps)	Rx Sensitivity (dBm)	Capacity* (kbps)
MSK	-116	9.6	-117	9.6
QPSK	-106	23	-110	17.5
8PSK	-101	34	-105	26
16QAM	-98	45	-102	35
32QAM	-94	57	-99	44

DATA CAPABILITIES

Packet handling	Layer 2 bridge
	Layer 3 static routes
	VLAN support
Error Correction	Up to 32-bit CRC, Retransmit on error
Data Encryption	128/256-bit AES
I/O and Serial Data Access	Optional I/O allows seamless integration of Modbus RTU and Modbus TCP protocols

MANAGEMENT

Web-based Interface via HTTP/HTTPS
LINKPlanner integration (capacity and availability planning)
Remote Management via SNMP
cnMaestro integration (roadmap)
Support for configuration files, remote software upgrades
Built-in diagnostic tools via web interface such as RF Ping and RF Throughput

* Capacities are over-the-air signalling rates. Usable throughput varies based on payload size, uplink/downlink ratio and protocol. UDP traffic is typically 55-60% of the over-the-air signalling rate.
 ** At 8W output transmit duty cycles are reduced depending on operating conditions.

** At 8W output transmit duty cycles are reduced depending on operating conditions.

INTERFACES

Ethernet Interfaces	2 x RJ-45
	10/100BaseT, Full Duplex, rate auto negotiated (802.3 compliant)
Serial Interfaces	2 x RJ-45
	RS-232/422/485, up to 230.4 kbps
Analog/Digital I/O (optional)	8 pins for analog input/output and digital input/output
RF / Antenna	TNC RF connectors (1 or 2 depending on single or dual-radio configuration)

POWER

Input	10-32VDC with reverse polarity protection						
Power Consumption (12VDC average)	3W Output			5W** Output			
	Transmit	Receive	Idle	Transmit	Receive	Idle	Idle
Single Radio Configuration (mA)	593	430	292	750	544		369
Dual Radio Configuration (mA)	620	467	311	784	591		393
IO Expander (mA)	293 mA						

PHYSICAL

Dimensions	6.625" x 3.45" x 1.835" (168 mm x 876 mm x 466 mm)						
Weight	Single Radio Configuration			1.54 lbs. (0.70 kg)			
	Dual Radio Configuration			1.61 lbs. (0.73 kg)			
DIN Rail Mount	optional						

ENVIRONMENTAL

Operating Temperature	-40C to +60C						
Humidity	95% operating humidity @ 40C non-condensing						
HAZLOC	UL-Approved to Class 1 / Div 2						

REGULATORY

UL	Approved						
FCC ID	Z8H89ft0026						
IC ID	109W-0025						

* Capacities are over-the-air signalling rates. Usable throughput varies based on payload size, uplink/downlink ratio and protocol. UDP traffic is typically 55-60% of the over-the-air signalling rate.

** At 8W output transmit duty cycles are reduced depending on operating conditions.