

[Print](#)



T7350H1009/U

Programmable Commercial Thermostat 3 Heat/3 Cool,

Overview

T7350H Communicating Thermostats control 24 Vac commercial single-zone multistage convecting modulating HVAC equipment. T7350H allows remote access and the sharing of system parameters in a LONWORKS® network.

Features

- 365-day programming.
- Two Occupied and two Not Occupied periods per day.
- Thermostat Interface Module (TIM) connections to thermostat from PDA for advanced configuration programming, keypad lockout, etc.
- Individual heat and cool setpoints available for Occupied and Not Occupied periods.
- P+I+D control minimizes temperature fluctuations.
- Recovery ramping control automatically optimizes equipment start times based on built-in algorithms.
- Universal Versaguard™ Thermostat guards available.
- Convenient overrides allow temporary setpoint changes.
- Keypad multi-level lockout available with all models.
- Remote sensor capability for temperature (including outdoor air and discharge air) and humidity.
- Auxiliary contact interfaces with a Honeywell Economizer System (for total rooftop condenser dehumidification output LONWORKS(R) network communication).

Product Specifications

Application	Conventional and Heat Pump systems
Comments	Remote Temp, Outdoor, Discharge Air, Humidity
Stages	3 Heat / 3 Cool
Switch Positions (System)	HEAT-OFF-COOL-AUTO-EM.HEAT
Switch Positions (Fan)	AUTO-ON
Color	Trident White

