



VIVE SUBMITTAL SHEET

Job Name: _____ Location: _____ Date: _____

Purchaser: _____ Installer: _____

Submitted to: _____ For: RNC R&R Commercial

MODEL TP-N-731W

Wireless Universal (Optimized for PTAC's)

Up to 1 Heat 1 Cool Conventional

Up to 2 Heat 1 Cool Heat Pump

Battery or Hardwire

Non-Programmable



This model features:

- 7 sq. inch display
- Blue backlight
- Glow in the dark light button
- Easy access battery compartment
- Universal subbase
- Simple private label badge system
- Setpoint limits
- Electric or gas configurable
- Mounts on wall or junction box
- Auto-changeover
- 5 Year Warranty
- 5 minute compressor delay protection (selectable on or off)
- Separate heating and cooling swing (cycle rate) adjustments
- Battery or 24V power
- Room temperature calibration adjustments
- Easy wire color coded terminal blocks
- Two and three speed fan options

Specifications:

| | |
|--------------------|---|
| Application | 1 Heat 1 Cool Conventional, 2 Heat 1 Cool Heat Pump |
| Programmability | Non-Programmable |
| System Switch | Cool - Off - Heat |
| Display Range | 41°F to 95°F (5°C to 35°C) |
| Control Range | 44°F to 90°F (7°C to 32°C) |
| Display Accuracy | +/- 1°F |
| Heat Swing | Adjustable from 0.2°F to 2.0°F |
| Cool Swing | Adjustable from 0.2°F to 2.0°F |
| Terminals | R, C, Y, W, O, B, GH, GL |
| Load Rating | 1 amp per terminal, 1.5 amp maximum all terminals combined |
| Power Source | 18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire) Battery power from 2 AA Alkaline batteries |
| Operating Ambient | 32°F to +105°F (0°C to +41°C) |
| Operating Humidity | 90% non-condensing maximum |
| Mounting | Wall or Junction Box |
| Dimensions | 4.7"W x 4.4"H x 0.8"D (119mm W x 112mm H x 20mm D) |
| Warranty | 5 year warranty |