



# VIVE SUBMITTAL SHEET

Job Name: \_\_\_\_\_ Location: \_\_\_\_\_ Date: \_\_\_\_\_

Purchaser: \_\_\_\_\_ Installer: \_\_\_\_\_

Submitted to: \_\_\_\_\_ For:  RNC  R&R  Commercial

## MODEL TP-P-605

### Single Stage

1 Heat, 1 Cool

Battery or Hardwire

7 Day or 5/1/1 Programmable



### This model features:

- 2 sq. inch display
- Blue backlight
- Glow in the dark light button
- Easy access battery compartment
- Setpoint limits
- Simple private label badge system
- Battery or 24v power
- 2 Year Warranty
- Seperate heating and cooling swing (cycle rate) adjustments
- 5 minute compressor delay protection (selectable on or off)
- Large Temperature and setpoint display
- Universal subbase

### Specifications:

Application	1 Heat, 1 Cool
Programmability	7 Day or 5/1/1 Programmable
Changeover	System Switch
Display Range	41°F to 95°F (5°C to 35°C)
Control Range	44°F to 90°F (7°C to 32°C)
Display Accuracy	+/- 1°F
Heat Swing	Adjustable from 0.2°F to 2.0°F
Cool Swing	Adjustable from 0.2°F to 2.0°F
Terminals	Rc, Rh, G, Y, W, O, B
Load Rating	1 amp per terminal, 1.5 amp maximum all terminals combined
Power Source	18 to 30 VAC, NEC Class II, 50/60 Hz for hardwire (common wire) Battery power from 2 AA Alkaline batteries
Operating Ambient	32°F to +105°F (0°C to +41°C)
Operating Humidity	90% non-condensing maximum
Mounting	Wall or Junction Box
Dimensions	4.7"W x 4.4"H x 1.1"D (119mm W x 112mm H x 28mm D)
Warranty	2 year warranty