



## 2.4/5 GHz Dual Band Rubber Duck With RPSMA Plug Connector

TerraWave's compact dual-band omnidirectional antenna offers wide coverage giving the user the ease and flexibility of having only one antenna for any type of access point. It features 3.5/6 dBi gain (2.4/5 GHz frequencies) and its rugged design makes it suitable for a wide variety of applications. Every TerraWave antenna is covered by the company's two-year TerraNet warranty program. For questions or to purchase product, contact your Regional Sales Executive at 210-375-8482, 800 -851-4965 or sales @terra-wave.com.

Specifications			
Frequency Range	2400~2500 MHz	4900~5875 MHz	
Bandwidth	100 MHz	975 MHz	
Gain	3.5 dBi	6 dBi	
Vertical Beamwidth	70°	50°	
Horizontal Beamwidth	360°	360°	
VSWR	2.0:	2.0 : 1 Max	
Nominal Impedance	50 C	50 Ohms	
Polarization	Linear,	Linear, Vertical	
Power Handling	2 W	2 W (cw)	
Connector	RPSM	RPSMA Plug	
Temperature	-10° C to	-10° C to +55° C	
Radome Color	Gray/Bla	Gray/Black/White	
Radome Material	ABS/I	ABS/Nylon	
Dimensions	5" x	5" x 0.95"	
Weight	0.05	0.05 lbs	



2.4 Ghz







5 Ghz

