

Job Name: _____

Date: _____

Location: _____

Approval: _____

Engineer: _____

Construction: _____

Submitted to: _____

Unit #: _____

Submitted by: _____

Drawing #: _____

Reference: _____



Specifications

Input Voltage.....	DC 12 V
Power Consumption.....	0.3 W
Display.....	3.8" backlit LCD display (255x160 dots) w/ touch panel
Usage Temperature Range.....	32° to 104°F (0° to 40°C)
Usage Humidity Range.....	20% to 90% (no condensation)
Storage Temperature Range.....	14° to 140°F (-10° to 60° C)
Storage Humidity Range.....	20% to 90% (no condensation)
Dimensions	
[H x W x D in. (mm)].	4-3/4 x 4-3/4 x 13/16 (120 x 120 x 20.4)
Weight.....	7.76 oz. (220 g)

General Features

- Operation modes: Auto/Cool/Dry/Fan/Heat
- Touch panel w/ backlit display
- Group & Individual Control
 - Up to 16 individual indoor units can be simultaneously controlled.
- User-friendly Operation
- Human Sensor Setting
 - Controls the temperature setting when no one is occupying the room & save energy costs.
 - Detects for people in the room by looking for movement with an infrared light
- Fan Control for Energy Saving
 - Fan operates intermittently and power is saved when set temperature is reached during cooling operation.
- Auto Off Timer Setting
 - Operation stops after the set time when indoor unit operation is started by the Operation button.
- Weekly Timer Setting
 - Weekly operation schedule can be set. Two schedule patterns can be created, up to 8 times setting for each day can be set.
- Additional Custom Settings:
 - Set temperature Auto Return
 - Set temperature Range Setting
 - Away Setting
 - Error History
 - Anti Freeze
 - Filter Reset
 - R.C. Master/Slave Setting
 - Language Setting

*Only compatible with Halcyon system 30RLXEH.

